

LEGEND

Existing Tree to be Retained	Existing Tree to be Removed	Existing Tree in poor condition to be Removed	Existing Dead Tree to be Removed	Undersize tree or Stump	Tree Protection Fencing



Tree Tag Legend
 XX = Tag number
 C=XX = Municipal tree
 OS=XX = Off-site tree
 S=XX = Straddling tree. Written permission required from owner to remove trees.
 XX=HP = Hand-plotted
 NT=XX = No Tag #



Arborist supervision is required for any work within 1.5 m of the tree protection barrier, including the excavation for proposed accessible access.

The stumps of the trees recommended for removal should be left in place.

SCHEDULE B
 Specification for Tree Protection Barriers



Notes:

- A protective barrier must be installed around every tree to be retained prior to the work commencing onsite, and that barrier must remain intact until the Director has authorized its removal.
- Maintenance of trees that are to remain must include watering.
- Any excavation adjacent to the protective barrier must be done by hand.
- Maintenance of trees that are to remain must include watering but will not include any cutting or pruning of branches or roots unless approved by the Director.
- The dimensions of the protective barrier must be equal to the extent of the drip line, or 30 cm per every 2.5 cm of tree caliper, whichever is greater.
- Measurements in relation to tree caliper must be taken at the base of the tree.

VDZ+A

FORT LANGLEY STUDIO MOUNT PLEASANT STUDIO
 100-9331 Church St. 100-355 Kingway
 Port Langley BC Vancouver BC
 V3M 2B8 V5T 3J7
 www.vdz.ca 604-882-0024

Note:

- Contact VDZ+A Project Arborist (Glyn Romaine - glyn@vdz.ca) for inspection 72 hrs prior to any grading or excavation within the tree protection zone, (typ) If during excavation it is found that it cannot be completed without severing roots that are critical to the trees health or stability it may be necessary to remove additional trees.
- Read this plan together with the arborist report prepared by VDZ+A.
- An additional 1m setback is shown for all hand-plotted trees to be retained.
- If Stump Grinding is to occur in close proximity to trees which are to be retained then it is requested stumps to be removed under Arborist supervision.
- It is the responsibility of the client or his/her representative to contact the project arborist for the purpose of:
 *Locating TPZ Fencing
 *Locating Work Zone and Machine access corridors where required
 *Reviewing the Report with the project foreman or site supervisor.

NOT FOR CONSTRUCTION

No.	By	Description	Date
4	AL	Revised for Arborist Report	2025-04-24
3	AL	Revised for Arborist Report	2025-03-28
2	AL	Revised for Arborist Report	2025-03-03
1	AL	Revised for Review	2025-02-14

No.	By	Description	Date
4	AL	Revised for Arborist Report	2025-04-24
3	AL	Revised for Arborist Report	2025-03-28
2	AL	Revised for Arborist Report	2025-03-03
1	AL	Revised for Review	2025-02-14

REVISIONS TABLE FOR DRAWINGS
 Copyright reserved. This drawing and design is the property of VDZ+A and may not be reproduced or used for other projects without permission.

No.	By	Description	Date
4	AL	Revised for Arborist Report	2025-04-24
3	AL	Revised for Arborist Report	2025-03-28
2	AL	Revised for Arborist Report	2025-03-03
1	AL	Revised for Review	2025-02-14

REVISIONS TABLE FOR SHEET

Project:
 Seaquam School Track Reno
 Location:
 11584 Lyon Rd, Delta, BC
 V4E 2K4

Drawn: AL	Stamp:
Checked: DGR	
Approved: MVDZ	Original Sheet Size: 24"x36"
Scale: 1:400	CONTRACTOR SHALL CHECK ALL DIMENSIONS ON THE WORK AND REPORT ANY DISCREPANCIES TO THE CONSULTANT IMMEDIATELY. THE CONSULTANT AND PROJECT ENGINEER ARE THE EXCLUSIVE REPRESENTATIVES OF THE OWNER AND SHALL BE RESPONSIBLE FOR THE CORRECTION OF ANY DISCREPANCIES. THE CONSULTANT SHALL BE RESPONSIBLE FOR THE CORRECTION OF ANY DISCREPANCIES. THE CONSULTANT SHALL BE RESPONSIBLE FOR THE CORRECTION OF ANY DISCREPANCIES.

Drawing Title:
 TREE MANAGEMENT PLAN



VDZ Project #:
 AR2025-03

Drawing #:
 AR-01

Z:\PROJECTS\ARBORIST\TRIMMING\SEQUAM SCHOOL TRACK RENOVATION\DWG\TTPM\TTPM-001-AR-01.dwg

1:400 0 4m 8 12 16 20 24 28 32 36 40 44 48 52 56 60